


## ANTI-TAMPER PLASTER FACED BEAD FRAME CTPB/AT



The Anti-Tamper lock system is designed to be used in areas where security against tampering is required. A leaf spring steel lock adds extra torque to the movement of the latch when opened or closed to assist in the prevention of tampering. This Access Panel has been tested to WCL2 by Bodycote Warringtonapt - certificate number 180468/B - where the Access Panel remained locked and maintained its integrity even after a variety of lockpicking and physical methods were used to force the door open.



**Anti-Tamper**  
Added security features to prevent tampering



**Maximum Protection**  
Full Polyester Powder Coating

### Composition

- Frame** ▶ 1mm zintec welded construction
- Door** ▶ 1mm zintec folded all sides for rigid door shell
- Coating** ▶ Fully Polyester Powder Coated RAL9010 Matt White  
Other colours available
- Lock** ▶ Anti-Tamper lock
- Depth** ▶ Frame Depth: 56mm  
Door Depth: 32mm


### Building Regulations

- Part L** ▶ **Thermal Resistance**  
BS EN ISO 10077-1:2006  
by Exova Warringtonapt
- Part E** ▶ **Burgular Resistance**  
WCL2  
by Bodycote Warringtonapt


Installer must follow guidelines set by the wall or ceiling manufacturer to ensure the correct properties are achieved for the environment. All tests have been conducted by independent UKAS accredited testing centres, further details available upon request.

# ANTI-TAMPER PLASTER FACED BEAD FRAME CTPB/AT

## Ceiling Environment



## Wall Environment



## Fitting Guidelines

To calculate a sufficient opening for the frame, we recommend adding 10mm to the door size supplied. Alternatively when ordering an Access Panel to suit an opening, take away 10mm from your opening dimension to calculate a door size.



Frame should be screw fixed into the wall or ceiling opening using fixing holes located on the sides of the frame.

It is recommended that sufficient independent bracing and support is obtained to ensure safe opening and closing of the access hatch within its environment.

## Please Note:

Drawing not to scale, reference purposes only. Components shown with an asterisk (\*) are suggestions only. Always refer to guidance provided by your wall or ceiling manufacturer.

## Legend

-  Plaster skim
-  Plasterboard

## Standard Shape and Sizes

Below is our range of sizes we manufacture as standard. Or use our bespoke manufacturing service for any other size or shape. Simply contact us with further details of your specification.

Door Size (mm)	Door Type	Structural Opening (mm)	Accessible Opening (mm)
150 x 150	Single	160 x 160	120 x 120
200 x 200	Single	210 x 210	170 x 170
300 x 300	Single	310 x 310	270 x 270
450 x 450	Single	460 x 460	420 x 420
550 x 550	Single	560 x 560	520 x 520
600 x 600	Single	610 x 610	570 x 570
600 x 300	Single	610 x 310	570 x 270
900 x 600	Single	910 x 610	870 x 570
1200 x 600	Single	1210 x 610	1170 x 570

## Extra Protection Against Moisture and Corrosion

All Ceildoor metal Access Panels and hatches are fully powder-coated white RAL 9010 in matt polyester paint. Even though the majority of Access Panels in the industry are used internally, Ceildoor ensures all our products are coated in full polyester powder which is normally recommended for general exterior situations, where good weathering resistance is required against high levels of atmospheric moisture or in particularly aggressive atmospheres.

## Security and Safety

It is extremely important to close and lock the Access Panel or hatch immediately after use. Failure to do so will affect and impair the performance of the environment where it has been installed in the event of fire.